




LED LIGHTING
LUMINAIRES


 **Verbatim**[®]
Technology you can trust

THE KAITEKI COMPANY Mitsubishi Chemical Holdings Group

	Part Number	Wattage (W)	Luminous flux (lm)	CCT (K)	Height (mm)	Outer Diameter (mm)	Inner Diameter (mm)	Lifetime (hrs)	Dimmable				
LED RECESSED DOWNLIGHTS										Voltage: 220-240V		CRI: ≥80	
	52412	11	600	3000	52.0	104	90	30,000	No				
	52413	12	680		52.0	119	105						
	52414	15	800		53.0	135	125						
	52415	21	1300		56.5	183	170						
	52416	24	1600	67.5	235	216							
	52448	11	850	4000	52.0	104	90	40,000	No				
	52449	15	1250		53.0	135	125						
	52450	21	1900		56.5	183	170						
52451	24	2150	67.5		235	216							
Accessories										52912 - Dimmable driver for 11W LED Recessed Downlight		52914 - Dimmable driver for 21W LED Recessed Downlight	
										52913 - Dimmable driver for 15W LED Recessed Downlight		52915 - Dimmable driver for 24W LED Recessed Downlight	
	Part Number	Wattage (W)	Luminous flux (lm)	Luminous intensity (cd)	CCT (K)	Beam Angle (°)	Tilting Angle (°)	Height (mm)	Outer Diameter (mm)	Inner Diameter (mm)	Housing Colour	Lifetime (hrs)	Dimmable
LED RECESSED SPOTLIGHTS										Voltage: 220-240V		CRI: ≥80	
	52404	12	720	3150	3000	25	30	55	112	75	White	30,000	Yes
	52405		710	1200		40							
	52406	12	720	3150	3000	25	30	55	112	75	Chrome	30,000	Yes
	52407		710	1200		40							
	Part Number	Wattage (W)	Luminous flux (lm)	Luminous intensity (cd)	CCT (K)	Beam Angle (°)	Tilting Angle (°)	Dimensions (mm)	Housing Colour	Lifetime (hrs)	Dimmable		
LED TRACKLIGHTS										Voltage: 220-240V		CRI: ≥80	
	52436	25	1750	3000	3000	40	180/350	217x156x115	White	35,000	No		
	52437	25	1900	3300				4000				217x156x115	
	52438	40	3000	6000	3000	40	180/350	214x177x118	White	35,000	No		
	52439	40	3100	6500	4000			214x177x118					
Accessories										52906 - Spot reflector 25° for LED Tracklight 25W		52908 - Honeycomb Louver for LED Tracklight 25W	
										52909 - Spot reflector 25° for LED Tracklight 40W		52911 - Honeycomb Louver for LED Tracklight 40W	
	Part Number	Wattage (W)	Luminous flux (lm)	Luminous intensity (cd)	CCT (K)	Beam Angle (°)	Tilting Angle (°)	Dimensions (mm)	Housing Colour	Lifetime (hrs)	Dimmable		
LED TRACKLIGHTS										Voltage: 220-240V		CRI: ≥80	
	52452	15	1200	2500	3000	40	180/350	152x86x128	White	50,000	Yes		
	52453	15	1300	2700				4000				152x86x128	
	52454	28	2400	6000	3000	40	180/350	199x112x168	White	50,000	Yes		
	52455	28	2600	6500	4000			199x112x168					
	52456	48	4100	7200	3000	40	180/350	197x143x209	White	50,000	Yes		
	52457	48	4600	8200	4000			197x143x209					
Accessories										52917 - Spot reflector 20° for LED tracklight 15W		52920 - Anti-glare snoot for LED tracklight 15W	
										52918 - Spot reflector 20° for LED tracklight 28W		52921 - Anti-glare snoot for LED tracklight 28W	
										52919 - Spot reflector 20° for LED tracklight 48W		52922 - Anti-glare snoot for LED tracklight 48W	

	Part Number	Wattage (W)	Luminous flux (lm)	CCT (K)	UGR	Dimensions (mm)	Housing Colour	Lifetime (hrs)	Dimmable
LED PANELS									
						Voltage: 100-240V		CRI: ≥80	
	52440	45	4000	4000	>19	595x595x46.5	White	50,000	No
	52441	45	3800	4000	<19	595x595x46.5	White	50,000	No
	52442	45	4000	4000	>19	622x622x46.5	White	50,000	No
	52443	45	3800	4000	<19	622x622x46.5	White	50,000	No

	Part Number	Wattage (W)	Luminous flux (lm)	Base	CCT (K)	Dimensions (mm)	Safety Class	Protection Class	Lifetime (hrs)	Dimmable
LED BATTEN LUMINAIRES WITH LED T8 TUBES										
						Voltage: 220-240V				
	52417	22	1950	G13	4000	40x52x1232	Class I	IP20	40,000	No
	52418	44	3800	G13	4000	40x52x1232	Class I	IP20	40,000	No
	52419	22	1700	G13	4000	86x72x1265	Class I	IP65	40,000	No
	52420	44	3100	G13	4000	86x115x1265	Class I	IP65	40,000	No

	Part Number	Base	Fitting	Dimensions (mm)	Safety Class	Protection Class	
LED BATTEN LUMINAIRES WITHOUT LED T8 TUBES							
	52430	G13	Single	86x72x1265	Class I	IP65	
	52431	G13	Twin	86x115x1265			
	52434	G13	Single	86x72x1565	Class I	IP65	
	52435	G13	Twin	86x115x1565			
	Accessories						
	52905 - Chain Suspension for Batten Luminaire IP65						

Verbatim - Denmark, Norway, Sweden, Finland and Iceland

Tobaksvejen 25, 2860 Søborg

Denmark

T: +45 7022 6323

F: +45 4590 7088

E: info.nordic@verbatim-europe.com

Verbatim - France and PortugalImmeuble Hermes, 20 rue Jacques Daguerre,
92565 Rueil-Malmaison Cedex**France**

T: +33 (0) 1 47 16 94 20

F: +33 (0) 1 47 16 15 00

E: info.france@verbatim-europe.com

www.facebook.com/VerbatimFrance

Verbatim - Germany, Austria & Switzerland, Central/East Europe

Düsseldorfer Str. 13, D - 65760 Eschborn,

Germany

T: +49 (0) 6196 900 10

F: +49 (0) 6196 900 120

E: info.germany@verbatim-europe.com

E: info.central-east@verbatim-europe.com

www.facebook.com/VerbatimDeutschland

Verbatim - Italy, Cyprus, Greece & Malta

Via Roma 108 , 20060 Cassina de' Pecchi MI,

Italy

T: +39 02 9530 1115

F: +39 02 9530 0449

E: info.italy@verbatim-europe.com

www.facebook.com/VerbatimItalia

**Московское представительство,
Verbatim – Russia, Commonwealth of
Independent States**Бизнес центр Golden Gate,
бульвар Энтузиастов, 2 109544**Москва**

T: +7 (495) 213 1980

F: +7 (495) 213 1978

E: info.east@verbatim-europe.com

www.facebook.com/VerbatimRussia

Verbatim - The Netherlands, Belgium & Luxembourg

Laan van Zuid Hoorn 14, 2289 DE Rijswijk,

The Netherlands

T: +31 (0)70 336 76 00

F: +31 (0)70 336 76 11

E: info.nl@verbatim-europe.com

Verbatim - Africa, Middle East & TurkeyFirst Floor, Building 4, Pinewood Office Park, 33 Riley Road,
Woodmead,**South Africa**

T: +27 (0) 11 253 4940

F: +27 (0)11 234 3626

E: info.sa@verbatim-europe.com

www.facebook.com/VerbatimSouthAfrica

www.facebook.com/VerbatimTurkiye

**Verbatim - United Kingdom, Ireland & Israel
(EMEA Head Office)**

Prestige House, 23-26 High Street, Egham, Surrey TW20 9DU,

United Kingdom

T: +44 (0) 1784 439 781

F: +44 (0) 1784 471 337

E: info.uk@verbatim-europe.com

www.facebook.com/VerbatimEurope

